


Package Outline Dimentions



KLHC2307W-7Watt

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	20V	V
Forward Current	IF	350	mA
Operating Temperature	Topr	-20~+80	°C
Storage Temperature	Tstg	-20~ +80	°C
Power Dissipation	Pd	8	Watt

Electro –Optical Characteristics (Ta=25°C)

Parameter	Test Condition	Symbol	Min	Typ	Max	Unit
CIE Coordinates	I=300mA	X	0.310	0.325	0.340
		Y	0.330	0.345	0.360	
Forward Voltage	I=300mA	Vf	22	23	23	V
Luminous flux	I=300mA	Φ	600	630	650	Lm
Color Temperature	I=300mA	Tc	5700	6000	6300	K
Viewing angle at 50% Iv	-----	2θ1/2	110	120	Deg
Reverse Current	Vr = 30V	Ir	10	µA
Color Rendering Index	I=300mA	CRI	70	72



KWALITY PHOTONICS PRIVATE LIMITED

ISO 9001-2008

29, EC Kushaiguda, Hyderabad-500 062. PH: 91-040-27123555, 27136252

sales@kwalityindia.com www.kwalityphotonics.com

RoHs