




PART NO.	Common Anode	CA														
	Common Cathode	CC	KLS31 I	KLS31 SR	KLS31 G	KLS31 SG	KLS31 SY	KLS31 SA	KLS31 UR	KLS31 SO	KLS31 B/UB	KLS31 BG	KLS31 UG	KLS31 W		
			KLS32 I	KLS32 SR	KLS32 G	KLS32 SG	KLS32 SY	KLS32 SA	KLS32 UR	KLS32 SO	KLS32 B/UB	KLS32 BG	KLS32 UG	KLS32 W		
OPERATING CHARACTERISTICS AT 25°C (Bigger Display may have more than one LED chip per segment)			UNITS	SYMBOL	I _{RED}	SUPER RED SR	GREEN G	SUPER GREEN SG	SUPER YELLOW SY	SUPER AMBER SA	ULTRA RED UR	SUPER ORANGE SO	BLUE B/UB	BLUE GREEN BG	ULTRA GREEN UG	WHITE W
Semiconductor Composition					AlGaAs			GaP/AlInGaP		AlInGaP			SiC / GaInN			
Forward Voltage - Typical @ 10mA			V	V _F	2.10	1.90	2.20	2.20	2.10	2.10	1.90	1.90	3.50	3.50	3.50	3.50
Forward Voltage - Maximum @ 20 mA			V	V _{FM}	2.40	2.10	2.60	2.40	2.40	2.40	2.10	2.40	4.50	4.50	4.50	4.50
Reverse Current @ V _R = 5V			μA	I _R	100	100	100	100	100	100	100	100	100	100	100	100
Peak Emission Wavelength			nm	λ _p	630	660	568	568	590	610	645	620	470	502	525	---
Emission Wavelength Half Width			nm	Δλ	35	20	30	15	15	15	20	20	25	30	35	---
Luminous Intensity per Segment			μcd	I _v	3500	6000	4000	6000	7000	7500	13000	13000	6000	7000	17000	---
ABSOLUTE MAXIMUM RATINGS AT 25°C																
Reverse Voltage			V	V _R	5	5	5	5	5	5	5	5	5	5	5	5
Forward Current (avg)			mA	I _F	20	20	20	20	20	20	20	20	20	20	20	20
Peak Forward Current (T<1μs)			mA	I _{FS}	80	80	80	80	80	80	80	80	80	80	80	80
Operating / Storage Temperature Range			-10° C to +85° C													
Lead Soldering Temperature			< 260° C for 5 Seconds													
Series Resistor to be used per segment			: 300 Ohms @ 5V Supply (OR) 50 to 100 Ohms @ 3V Supply													

ELECTRICAL CHARACTERISTIC CURVES



1. AlGaAs : I, SR

2. GaP : G

3 & 4. AlInGaP : SG, SY, SA, UR, SO

5. GaInN : B, BG, UG, W